



RISO ComColor® FW Series Printers

Increase the speed and impact of your communications.



Keep your print and mail moving.

Your business depends on sending transactional documents, like bills and statements, to your customers. Meet your deadlines and accelerate your printing processes with the RISO ComColor® FW inkjet printer.


Improving uptime has never been cooler.

Older print technologies, like toner-based copiers and printers, use heat to print. This creates static and causes paper to curl, causing jams and other maintenance issues that delay your workflow. More time is wasted waiting for printed pages to cool down before using your folding and inserting systems, all of which prevents important communications from reaching customers on time, especially during high-volume print runs.


The RISO ComColor FW prints your documents reliably using heatless inkjet printing, so you can fold and insert your mail without delays. It uses innovative inkjet technology coupled with a simple straight paper path. Paper is printed cold, fast, and flat for continuous operation and maximized uptime in your full print-to-mail process.

Accelerate your print to mail process

Traditional laser printing



RISO ComColor FW Series





Add more value to your communications while staying within your budget.

Print faster and more reliably.

The ComColor® FW Series helps ensure your mail is no longer waiting on your copier. With processing speeds of up to 120ppm, the ComColor FW Series prints your documents quickly, without slowing down for duplex or color printing. Now, even the highest volume production printing needs can be handled fast and reliably.

ComColor FW5000



ComColor FW5230



ComColor FW5231



90 pages per minute

3 feed trays

2000 sheet capacity

120 pages per minute

3 feed trays

2000 sheet capacity

120 pages per minute

1 feed tray

1000 sheet capacity

Improve your communications with color.

Boost customer engagement.

Most of your customer interactions—your website, mobile app and email—are in full color. Yet, your printed communications continue to lag behind in black and white. Have a more productive conversation with customers with full color. Use color to highlight special announcements, call out new features or emphasize relevant offers. Plus, by leveraging the high open-rate of transactional communications, your audience is more likely to respond to offers. Most importantly, color allows you to give your customers consistent branding and messaging across physical and digital touch-points.

Color output with black and white costs.

Typical businesses have perceived color as being too expensive and too slow. It's not any more. Now, you can add the value of color to your communications without decreasing profitability. The ComColor® FW prints full color transactional documents faster—and for much less—than your current copiers. Its inkjet technology adds the engaging color that your customers want for a similar cost to black and white print without any reduction in rated speeds.



Sample black and white statement



Sample color statement



Improve customer satisfaction

According to InfoTrends¹, 38% of consumers want color to emphasize important information on the communications you send. Making your documents easier to understand helps customers quickly identify the information you want them to know, thus improving customer satisfaction.

Double response

by adding revenue generating cross-sell offers to the statement².



¹ InfoTrends 2014

² Pitney Bowes Client Success Measure

Optional accessories to customize your workflow.

The ComColor® FW Series offers flexible options to suit your print finishing and management needs.

Face Down Finisher F10

Compact finisher exclusively for offset stacking and stapling finished prints.

Scanner HS7000

The auto feeder enables copying and scanning of duplex originals of up to 200 sheets¹ at a time. Output formats include PDF, TIFF, JPEG and PDF/A.

Multifunction Finisher FG10

Intelligent inline functions performed automatically simplify the finishing process.

RISO Auto-Control Stacking Tray II

The paper guides automatically open to the correct width to match the paper in use.

PS Kit FG10

When the PS Kit is installed, several functions useful for more efficient use—such as Tray Selection Per Page, Color Profile, Form Overlay—are available.

Wide Stacking Tray

Wider paper can be printed and stacked in a wider tray to match the paper in use.

IC Card Authentication Kit II

The optional IC Card Authentication Kit enables user management using an IC card.



¹ 80 gsm (21-lb bond) or less.



Staple and offset stacking



Tray II



Wide stacking tray



Staple and hole punch

	FW5000	FW5230	FW5231
Print speed ¹	Simplex: Up to 90 ppm Duplex: Up to 45 sheets/min (90 pp)	Simplex: Up to 120 ppm Duplex: Up to 60 sheets/min (120 pp)	Simplex: Up to 120 ppm Duplex: Up to 60 sheets/min (120 pp)
Sheet capacity	2000 sheets (1000 standard tray, 500 sheet drawer x 2)	2000 sheets (1000 standard tray, 500 sheet drawer x 2)	1000 sheets (standard tray)
Print resolution	Up to 300 x 600 dpi	Up to 300 x 600 dpi	Up to 300 x 600 dpi
Print area	8 3/16" X 12 13/32" (210mm x 544mm)	12 3/16" X 21 13/32" (310mm x544mm)	12 3/16" X 21 13/32" (310mm x544mm)
Media weight	12-lb to 56-lb bond (46 gsm to 210 gsm)	12-lb to 56-lb bond (46 gsm to 210 gsm) ²	12-lb to 56-lb bond (46 gsm to 210 gsm)
Ink	Oil-based pigment ink (CMYK)	Oil-based pigment ink (CMYK)	Oil-based pigment ink (CMYK)
Print technology	FORCEJET™ in-line inkjet print heads	FORCEJET™ in-line inkjet print heads	FORCEJET™ in-line inkjet print heads
Duty cycle ³	Up to 500,000 pages per month	Up to 500,000 pages per month	Up to 500,000 pages per month
Dimensions	In use: 40 19/32"L x 28 9/16"W x 43 29/32"H (1,030mm L x 725mm W x 1,115mm H)	In use: 40 19/32"L x 28 9/16"W x 43 29/32"H (1,030mm L x 725mm W x 1,115mm H)	In use: 40 19/32"L x 28 9/16"W x 43 29/32"H (1,030mm L x 725mm W x 1,115mm H)
Power source	AC 100-240V (Standard 110V outlet)	AC 100-240V (standard 110V outlet)	AC 100-240V (Standard 110V outlet)

¹ When using plain paper and recycled paper (85 gsm (23-lb bond)), and density setting 3 (Standard). Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6]]. The continuous print speed varies depending on the type of optional output accessories connected.

² The margin when printing envelopes is 10 mm (3/8"). The guaranteed area when printing images is the area enclosed within 5 mm (7/32") of the edges of the paper.

³ Average expected monthly cycle count is 300,000 cycles per month with an occasional increase of cycles up to the maximum 500,000.



United States

3001 Summer Street Stamford, CT 06926-0700

For more information, visit us online: pitneybowes.com

Pitney Bowes and the Corporate logo are trademarks of Pitney Bowes Inc. or a subsidiary. All other trademarks are the property of their respective owners.

© 2015-2016 Pitney Bowes Inc. All rights reserved.

